

# Document made available under the Patent Cooperation Treaty (PCT)

International application number: PCT/EP05/050611

International filing date: 11 February 2005 (11.02.2005)

Document type: Certified copy of priority document

Document details: Country/Office: EP  
Number: 04003270.8  
Filing date: 13 February 2004 (13.02.2004)

Date of receipt at the International Bureau: 25 February 2005 (25.02.2005)

Remark: Priority document submitted or transmitted to the International Bureau in compliance with Rule 17.1(a) or (b)



World Intellectual Property Organization (WIPO) - Geneva, Switzerland  
Organisation Mondiale de la Propriété Intellectuelle (OMPI) - Genève, Suisse



Europäisches  
Patentamt

European  
Patent Office

Office européen  
des brevets

Bescheinigung

Certificate

Attestation

Die angehefteten Unterlagen stimmen mit der ursprünglich eingereichten Fassung der auf dem nächsten Blatt bezeichneten europäischen Patentanmeldung überein.

The attached documents are exact copies of the European patent application described on the following page, as originally filed.

Les documents fixés à cette attestation sont conformes à la version initialement déposée de la demande de brevet européen spécifiée à la page suivante.

Patentanmeldung Nr.    Patent application No.    Demande de brevet n°

04003270.8

Der Präsident des Europäischen Patentamts;  
im Auftrag

For the President of the European Patent Office

Le Président de l'Office européen des brevets  
p.o.

R C van Dijk



Anmeldung Nr.:  
Application no.: 04003270.8  
Demande no.:

Anmeldetag:  
Date of filing: 13.02.04  
Date de dépôt:

Anmelder/Applicant(s)/Demandeur(s):

Shell Solar GmbH  
Otto Hahn Ring 6  
81739 München  
ALLEMAGNE

Bezeichnung der Erfindung/Title of the invention/Titre de l'invention;  
(Falls die Bezeichnung der Erfindung nicht angegeben ist, siehe Beschreibung.  
If no title is shown please refer to the description.  
Si aucun titre n'est indiqué se référer à la description.)

Applying a liquid dopant solution on a wafer

In Anspruch genommene Priorität(en) / Priority(ies) claimed / Priorité(s)  
revendiquée(s)  
Staat/Tag/Aktenzeichen/State/Date/File no./Pays/Date/Numéro de dépôt:

Internationale Patentklassifikation/International Patent Classification/  
Classification internationale des brevets:

H01L21/00

An Anmeldetag benannte Vertragsstaaten/Contracting states designated at date of  
filing/Etats contractants désignées lors du dépôt:

AT BE BG CH CY CZ DE DK EE ES FI FR GB GR HU IE IT LU MC NL  
PT RO SE SI SK TR LI

13. Feb. 2004

- 1 -

TS 9537 EPC

Hsb

## APPLYING A LIQUID DOPANT SOLUTION ON A WAFER

The present invention relates to applying a liquid dopant solution on the surface of a wafer. Such a wafer is suitably a silicon wafer used in manufacturing a photovoltaic cell.

5        When a wafer is used in manufacturing a photovoltaic cell, it is provided with a bulk doping. One of the two surfaces of the wafer is designated as light receiving surface, and the side of the wafer is the light receiving side. At its light receiving side the wafer is provided  
10       with a thin layer having a doping that differs from the bulk doping. The transition between the bulk and the thin region is called a junction.

      There is a tendency to apply a doping as well on the backside of the wafer (the side of the wafer opposite the  
15       light receiving side). This is done to create a so-called back surface field, which is a build-in electric field on the backside that deflects minority carriers and reduces the recombination rate at the back surface.

      A thin doped layer at the light receiving side of the  
20       wafer or at its back side can be obtained in three ways:  
      (1) depositing the dopant in gaseous form at elevated temperature and allowing the gaseous dopant to diffuse into the wafer, (2) applying a dopant-containing paste on the surface of the wafer and heating the wafer to cause  
25       the dopant to diffuse into the wafer, and (3) applying a liquid dopant solution on the surface of the wafer and heating the wafer with the dopant solution on it to evaporate the solvent and to cause the dopant to diffuse into the wafer.

Applying a liquid dopant solution can be done with different techniques. One technique is spraying the liquid dopant solution on the surface of a wafer, and another technique is dropping a small volume of liquid dopant solution on the surface of a spinning wafer and allowing the liquid dopant solution to spread evenly over the surface.

The present invention is also concerned with applying the liquid dopant solution on the surface of a wafer.

The production rate, which is the number of wafers that can be provided with the dopant solution, of the known techniques is low. In order to reduce the costs of solar energy a higher production rate is required.

It is an object of the present invention to provide a device for applying a liquid dopant solution on the surface of a wafer that allows a high production rate.

To this end the device for applying a liquid dopant solution on the surface of a wafer, which device comprises a dopant distribution device, a rotatable dopant-transfer roll horizontally translatable in a direction perpendicular to the axis of rotation of the dopant-transfer roll between a first roll position and a second roll position, and a work table for holding during normal operation the wafer to be provided with the dopant solution, wherein the distribution device comprises a dopant-transfer block supported by a block holder and a fluid container having an open side enclosed by an edge, which open side is directed to the dopant-transfer block and which edge cooperates with the dopant-transfer block, the block holder or both to prevent leaking of dopant solution, wherein the block holder and the fluid container can be displaced relative to each other, wherein the block holder is horizontally translatable in a direction perpendicular to the axis of rotation of the dopant-transfer roll between a first block position in

which the dopant-transfer block is under the open side of the fluid container and a second block position in which the dopant-transfer block has contacted the rotatable dopant-transfer roll in its first roll position, wherein during normal operation in the second roll position the rotatable dopant-transfer roll has contacted the wafer to provide dopant solution onto the surface of the wafer.

For the sake of completeness reference is made to USA patent specification No. 4 557 195. This publication relates to a device for printing an object, which device includes a device for inking a printing block. The known device comprises an ink distribution device comprising a printing block supported by a block holder and an ink container having an open side enclosed by an edge, which open side is directed to the printing block and which edge cooperates with the printing block and the block holder to prevent leaking of ink, wherein the block holder and the ink container can be displaced relative to each other, wherein the block holder is horizontally translatable between a first block position in which the printing block is under the open side of the ink container and an exposed position in which the printing block is free from the fluid container.

During normal operation, the printing block (also called cliché), which is engraved, is kept stationary, and the ink container displaced from the first position, in which the printing block is inked, to the exposed position. In the exposed position, a rubber pad is pressed on the printing block to accept the ink from the printing block. After accepting the ink, the pad is turned away to print an object.

An alternative to the above device is disclosed in International patent application publication No. 93/09 950. The device disclosed in this publication differs from the above-described device for inking a

printing block in that during normal operation the printing block is kept stationary and the ink container is displaced relative to the printing block.

5 The invention will now be discussed by way of example in more detail with reference to the accompanying drawing, wherein Figures 1a, 1b and 1c show schematically and not to scale the device for applying a liquid dopant solution according to the present invention in three different operation positions.

10 The device 1 for applying a liquid dopant solution on the surface of a wafer 3 comprises a dopant distribution device 5, a rotatable dopant-transfer roll 7, and a worktable 9 for holding during normal operation the wafer 3 to be provided with the dopant solution.

15 The rotatable dopant-transfer roll 7 is horizontally translatable in a direction perpendicular to the axis of rotation 12 of the dopant-transfer roll 7 between a first roll position 15 and a second roll position 17. Please note that the axis 12 extends perpendicular to the plane of drawing.

20 The distribution device 5 comprises a dopant-transfer block 20 supported by a block holder 21 and a fluid container 24 having an open lower side enclosed by a sealing edge 26. The open side is directed to the dopant-transfer block 20. The sealing edge 26 cooperates with  
25 the dopant-transfer block 20, the block holder 21 or with both the dopant-transfer block 20 and the block holder 21 to prevent leaking of dopant solution.

30 The block holder 21 supporting the dopant-transfer block 20 and the fluid container 24 can be displaced relative to each other. The block holder 21 is horizontally translatable in a direction perpendicular to the axis of rotation 12 of the dopant-transfer roll 7 between a first block position 30 in which the dopant-transfer block 20 is under the open side of the fluid  
35

container 24 and a second block position 31 in which the dopant-transfer block 20 has contacted the rotatable dopant-transfer roll 7 in its first roll position 15.

5       The second roll position 17 of the rotatable dopant-transfer roll 7 is so selected that in the second roll position 17 the dopant-transfer roll 7 has contacted the wafer 3 to provide dopant solution onto the surface of the wafer 3.

10       Means for supporting and guiding the block holder 21 and the dopant-transfer roll 7 and means for supporting the worktable 9 are not shown in the Figures.

15       During normal operation, a wafer 3 to be provided with a dopant solution is secured on the worktable 9. The fluid container 24 is filled with dopant solution. The block holder 21 is in its first block position 30 and the dopant-transfer roll 7 is in its first position 15. In its first position the block 20 is under the open side of the fluid container and dopant solution can wet the dopant-transfer block 20. This initial position is shown in Figure 1a.

20       Then the block holder 21 is translated horizontally in a direction perpendicular to the axis of rotation 12 of the dopant-transfer roll 7 from the first block position 30 to the second block position 31 in which the dopant-transfer block 20 has contacted the rotatable dopant-transfer roll 7 in its first roll position 15. This position is shown in Figure 1b. The sealing edge 26 cooperating with the block 20, the block holder 21 or with both prevents leakage of the dopant solution.

30       During the translation of the block holder 21, the dopant-transfer roll 7 is lifted up so that the dopant-transfer block 20 moves under the dopant-transfer roll 7. The size of the dopant-transfer block 20 in the direction of its translation is at least equal to the circumference of the dopant-transfer roll 7.

35



Then the rotatable dopant-transfer roll 7 is lowered so as to bring it into contact with the dopant-transfer block 20, and then the rotatable dopant-transfer roll 7 is translated horizontally in a direction perpendicular to the axis of rotation 12 of the dopant-transfer roll 7 from the first roll position 15 to the second roll position 17. In the second roll position 17 the dopant-transfer roll 7 has contacted the wafer 3 to provide dopant solution onto the surface of the wafer 3. This is the final position and it is shown in Figure 1c.

During part of the translation, the dopant-transfer roll 7 moves over and in contact with the dopant-transfer block 20, and dopant solution is transferred unto the dopant-transfer roll 7. The dopant solution on the dopant-transfer roll 7 is during the last part of the translation transferred on the surface of the wafer 3 that is to be provided with dopant solution. Suitably the circumference of the dopant-transfer roll 7 is about equal to the size of the wafer 3 in the direction of translation of the dopant-transfer roll 7.

Then the dopant-transfer roll 7 and the block holder 21 return to their respective first positions, as shown in Figure 1a, the wafer 3 provided with the dopant solution is removed and a new wafer is put in the worktable.

It will be understood that the initial position as shown in Figure 1a can also be reached by returning the block holder 21 to the first block position 30 simultaneously with translating the dopant-transfer roll 7 to the second roll position 17, after which the dopant-transfer roll 7 is returned to the first roll position 15.

Suitably, the dopant-transfer block 20 is made of plastic, steel or a ceramic material and it is provided

with a suitable structure. The dopant-transfer roll 7 is suitably made of a silicone rubber.

The surface of the wafer on which the dopant solution is applied can be a flat surface or a structured surface.

5       The device according to the present invention allows doping about 1 000 wafers per hour. Moreover, the present invention allows applying a thin uniform layer of the dopant solution, wherein the thickness of the layer of dopant solution is between 1 and 10 micrometer. The layer  
10       can be applied over a large surface area (more than 100 cm<sup>2</sup>) and on thin wafers (less than about 100 micrometers).

13. Feb. 2004

TS 9537 EPC

C L A I M

1. A device for applying a liquid dopant solution on the surface of a wafer, which device comprises a dopant distribution device, a rotatable dopant-transfer roll horizontally translatable in a direction perpendicular to the axis of rotation of the dopant-transfer roll between  
5 a first roll position and a second roll position, and a work table for holding during normal operation the wafer to be provided with the dopant solution, wherein the distribution device comprises a dopant-transfer block supported by a block holder and a fluid container having  
10 an open side enclosed by an edge, which open side is directed to the dopant-transfer block and which edge cooperates with the dopant-transfer block, the block holder or both to prevent leaking of dopant solution, wherein the block holder and the fluid container can be  
15 displaced relative to each other, wherein the block holder is horizontally translatable in a direction perpendicular to the axis of rotation of the dopant-transfer roll between a first block position in which the dopant-transfer block is under the open side of the fluid  
20 container and a second block position in which the dopant-transfer block has contacted the rotatable dopant-transfer roll in its first roll position, wherein during normal operation in the second roll position the  
25 rotatable dopant-transfer roll has contacted the wafer to provide dopant solution onto the surface of the wafer.

13. Feb. 2004

TS 9537 EPCA B S T R A C T

## APPLYING A LIQUID DOPANT SOLUTION ON A WAFER

Device (1) for applying a liquid dopant solution on a wafer (3), comprising a dopant distribution device (5), a rotatable horizontally translatable dopant-transfer roll (7) between a first roll position (15) and a second roll position, and a work table (9) for holding the wafer (3), wherein the distribution device (5) comprises a dopant-transfer block (20) and a fluid container (24) having an open side enclosed by an edge (26), which open side is directed to the dopant-transfer block (20), wherein the block holder (21) is horizontally translatable between a first block position in which the dopant-transfer block is under the open side of the fluid container and a second block position (31) in which the dopant-transfer block (20) has contacted the rotatable dopant-transfer roll (7) in its first roll position (15), wherein during normal operation in the second roll position the rotatable dopant-transfer roll (7) has contacted the wafer (3) to provide dopant solution onto the surface of the wafer (3).

(Figure 1b)

TS 9537

13. Feb. 2004

